



QUALITY ENGINEERED FOR HOME USE



MODEL	LYNX-52	LYNX-62	LYNX-70	LYNX-74
WORKING WIDTH	52"	62"	70"	74"
HORSE POWER RECOMMENDED (HP)	16 to 25 hp		25 to 35 hp	
CUTTING HEIGHT	25"		29"	
HEIGHT - CHUTE BASE	27"		31"	
DRUM DIAMETER	21"		22"	
DRUM DEPTH	6"		8"	
IMPELLER BLADES	4			
SHEAR BOLT	1 on the main PTO + 1 on the auger			
SIZE OF IMPELLER SHAFT	1"		1 1/4"	
HEIGHT - IMPELLER CENTER	13"		14"	
IMPELLER RPM	540			
AUGER	14" diam.		16" diam.	
DRIVE CHAIN	50		60	
CHUTE ROTATION	Standard manual - optional hydraulic cylinder			
HITCH CATEGORY	Category 1		Cat. 1 & 2	
STANDARD SCRAPER BLADE	3/8" x 1"		3/8" x 1 1/2"	
OPTIONAL SKID SHOES	Adjustable bolts			
CHUTE	Choice of manual or hydraulic deflector			
AUGER BEARINGS	1"		1 1/4"	
WEIGHT	Approx. 303 lbs	Approx. 319 lbs	Approx. 333 lbs	Approx. 472 lbs

CHARACTERISTICS



Manual chute rotation



Gear-to-gear hydraulic chute rotation with cylinder



Proven engineering

Les Équipements Hardy inc.
100 rue Saint-Arthur, Portneuf, Québec, G0A 2Y0, Canada
Tel.: 418-286-6621 • Fax: 418-286-3733
info@gohardy.com

www.gohardy.com

AUTHORIZED DEALER: